



An Oshkosh Corporation Company

April 10, 2019

### JLG BOOM LIFT PLATFORM NETTING INSTALLATION TO TOP RAIL

#### To Whom it May Concern

Pursuant to requests and information received, JLG Industries, Inc. submits the following:  
JLG approves of the installation of non-JLG supplied mesh to the top rail of the platform on the following ANSI specification machines manufactured after 2003:

#### Models Affected

- 340AJ
- 400S/460SJ
- 450A/AJ
- 450A/AJ Series II
- 400SC/460SJC
- 510AJ Series II
- 520AJ
- 600A/AJ
- 600A Narrow/AJ Narrow
- 600S/660SJ
- 600SC/660SJC
- 740AJ
- 800A/AJ
- 800S
- 810SJ
- 860SJ
- 1200SJP
- 1250AJP
- 1350SJP
- 1500AJP
- 1500SJ
- 1850SJ

The above described modification shall be authorized provided that the following criteria are adhered to:

- The entity performing the modification is responsible for the workmanship of modifications and the selection, quality, and performance of the components utilized.
- The mesh must be attached through a method that does not require drilling or welding.
- The mesh is not permitted to be installed on the underside of the platform.
- Proper operation of gates, hinges or other mechanisms must not be adversely affected. Access to the platform through the gate area(s) must not be impeded.
- Mesh must not interfere with the platform controls.
- The mesh must be flame-retardant.
- The weight of the mesh and means of fastening to the platform must not exceed 20 lb. and be considered as part of the platform load.

#### JLG Customer Support

North America @ 1-877-554-5438 ■ Europe, Africa & Middle East @ +31 (0)23 569 8751 ■ Australia @ +61 2 6581 1111  
Brazil @ +55 19 3295 0407 ■ Singapore @ +65 6591 9030 ■ Hong Kong @ (852) 2639 5783



An Oshkosh Corporation Company

**TIB 19-09**

- 
- Do not operate machines with mesh installations when wind conditions, including gusts, may exceed 15 mph.
  - The transmittance/openness of the mesh must be greater than 40%.
  - Mesh hole opening must not exceed ¼".
  - Mesh pattern must be consistent.

Current owners of JLG products are responsible for the safe and proper operating condition of the subject boom lifts. Please consult with your local, state, and employer regulations for any additional requirements. It is the owner's/user's responsibility to ensure that JLG products are used as intended.

The operator is responsible for the safe and proper operation and utilization of the aerial work platform. JLG Industries, Inc. assumes no responsibility or liability for any and all incidents involving personal injury, property damage, or equipment damage that may occur from the improper utilization of JLG products.

Should you have any questions or require additional information, please advise.

Sincerely,

JLG INDUSTRIES, INC.

Product Safety and Reliability Department

Telephone: 877-JLG-SAFE

Facsimile: 301-745-3713

E-mail Address: [productsafety@jlg.com](mailto:productsafety@jlg.com)